




Floor standing storage electric water heater



- TITANIUM GLASSLINED STEEL INNER TANK TESTED AT 12 BAR
- 5 BOLTS EXTRA LARGE INSPECTION FLANGE
- OVERSIZED MAGNESIUM ANODE
- THERMOSTAT WITH BIPOLAR SAFETY DEVICE
- PRESSURE SAFETY VALVE TESTED AT 7 BAR
- SUPPLIED WITH SAFETY RELIEF VALVE

floor standing

Technical data - Overall dimensions

		ARI 200 STAB	ARI 250 STAB	ARI 300 STAB	TI STI 500					
		ARI 200 STAB	ARI 250 STAB	ARI 300 STAB	TI STI 500	ARI 200 STAB	ARI 250 STAB	ARI 300 STAB	TI STI 500	
Capacity	l	200	250	300	500	a mm	1320	1270	1800	1870
Power	W	3000	3000	3000	6	b mm	560	560	560	710
Voltage	V	230/400	230/400	230/400	230/400	c mm	390	365	365	335
Heating time ($\Delta T=45^{\circ}\text{C}$)	h, min.	4,26	5,00	5,54	4,40	d mm	-	-	-	-
Max. Working Temp.	$^{\circ}\text{C}$	75	75	75	75	e mm	-	-	-	-
Heat dispersion	kWh/24h	1,88	2,17	2,6	3,6	f mm	-	-	-	-
Max. Working Pressure	bar	8	8	8	8	g mm	-	-	-	-
Weight	kg	50	61	71	95					

ARI 200 STAB
3200298

ARI 250 STAB
3010139

ARI 300 STAB
3200300

TI STI 500
828016

