



Wall-hung electric storage water heater vertical and horizontal versions available



- GLASSLINED INNER TANK
- EXTERNAL TEMPERATURE CONTROL KNOB
- 15 LITERS OF EXTRA HOT WATER AT 40°C PLUS
- LARGE MAGNESIUM ANODE
- ORIGINAL ARISTON THERMOSTAT WITH BUILT-IN SAFETY DEVICE
- CALCIUM-PROOF HEATING ELEMENT
- SAFETY VALVE RATED AT 8 BAR
- INNER TANK TESTED AT 16 BAR

good looking

Technical data - Overall dimensions

		BLU R						BLU R						
		50 V	80 V	100 V	50 H	80 H	100 H	50 V	80 V	100 V	50 H	80 H	100 H	
Capacity	l	50	80	100	50	80	100	a mm	603	808	961	603	808	961
Power	W	1500	1500	1500	1200	1500	1500	b mm	497	497	497	494	494	494
Voltage	V	230	230	230	230	230	230	c mm	469	497	467	467	494	494
Heating time (T= 45°C) h, min.		1.50	2.56	3.40	2.17	2.56	3.40							
Max. Working Temp.	°C	75	75	75	75	75	75							
Heat dispersion	kWh/24h	0.96	1.22	1.39	1.02	1.48	1.65							
Max. Working Pressure	bar	8	8	8	8	8	8							
Weight	kg	17	23	25	17	23	25							
Inner Tank Steel Thickness (average)	mm	1.8	1.8	1.8	1.8	1.8	1.8							
Insulation Thickness (average)	mm	20	20	20	20	20	20							
Protection	IP	X3	X3	X3	X1	X1	X1							

BLU R 50 V
3605199





BLU R 80 V
3605200

BLU R 100 V
3605201

BLU R 50 H
3605202

BLU R 80 H
3605203

BLU R 100 H
3605204



legend

E cold water inlet G 1/2"

U hot water outlet G 1/2"