



Wall-hung electric storage water heater



GUARANTEE OF QUALITY



POLYURETHANE INSULATION



ENAMELLED STEEL TANK

- EXCLUSIVE DESIGN
- HIGH QUANTITY OF HOT WATER MIXED
- NEW STRONG THERMOMETER
- THERMOSTAT WITH BIPOLAR SAFETY DEVICE
- OVERSIZE MAGNESIUM ANODE
- HIGH EFFICIENCY WITH EXPANDED POLYURETHANE INSULATION
- PRESSURE SAFETY VALVE TESTED AT 8 BAR
- PRODUCT TESTED TO THE HIGHEST QUALITY STANDARDS
- GLASSLINED INNER TANK TESTED AT 16 BAR

ease
guaranteed

Technical data - Overall dimensions

| | PRO R | | | | | | | PRO R | | | | | |
|-------------------------|------------|------------|-------------|------------|------------|-------------|---------|-------|------|-----|------|-----|-----|
| | PRO R 50 V | PRO R 80 V | PRO R 100 V | PRO R 50 H | PRO R 80 H | PRO R 100 H | 50V | 80V | 100V | 80H | 100H | | |
| Capacity | l | 50 | 80 | 100 | 50 | 80 | 100 | | | | | | |
| Installation | | V | V | V | H | H | H | a mm | 553 | 758 | 913 | 758 | 913 |
| TD/TS | | - | - | - | - | - | - | b mm | 398 | 603 | 758 | - | - |
| Size | | Regular | Regular | Regular | Regular | Regular | Regular | c mm | - | - | - | 174 | 177 |
| Power | kW | 1,5 | 1,5 | 1,5 | 1,2 | 1,5 | 1,5 | d mm | - | - | - | 335 | 487 |
| Voltage | V | 230 | 230 | 230 | 230 | 230 | 230 | | | | | | |
| Heating time (ΔT=45°C) | h,min | 1:50' | 2:56' | 3:40' | 2:17' | 2:56' | 3:40' | | | | | | |
| Heat dispersion at 65°C | kWh/24h | 0,96 | 1,22 | 1,39 | 1,02 | 1,48 | 1,65 | | | | | | |
| Max working pressure | bar | 8 | 8 | 8 | 8 | 8 | 8 | | | | | | |
| Max working temperature | °C | 75 | 75 | 75 | 75 | 75 | 75 | | | | | | |
| Weight | kg | 16 | 21,5 | 25 | 16 | 21,5 | 25 | | | | | | |
| Protection | IP | X3 | X3 | X3 | X1 | X1 | X1 | | | | | | |

PRO R 50 V
3200423





PRO R 80 V
3200424

PRO R 100 V
3200425

PRO R 50 H
3200426

PRO R 80 H
3200427

PRO R 100 H
3200428



LEGEND

E Cold water inlet G 1/2"

U Hot water outlet G 1/2"

T Thermoelectric inlet/outlet pipes G 3/4"